SPECIFICATION SHEETS

OS500LED

OUTDOOR SECURITY SOLUTIONS FOR RESIDENTIAL APPLICATION

NAME:	
TYPE:	
DATE:	
NOTES:	

SPECIFICATIONS

LIGHT UNIT:	Poly-carbonate housing and lens, corrosion-resistant, in either dark bronze or white for lasting durability. LED lamp head is isolated from the driver. It is located in the rear housing, promoting a long service life. The lens is sealed to keep out moisture, dirt and bugs. LEDs maintain 70% of light output at 50,000 hours of service life
INSTALLATION:	Mounts to a recessed junction box on a wall. Crossbar and hardware provided. Wet location listed for mounting 4 feet above ground.
ELECTRICAL:	Energy efficient LED provides 1200 lumens, consumes 18W utilizing 120V 60Hz driver. Dusk-to-dawn photocell provided as a standard. Rated for outdoor installations, -40ºC minimum ambient. LISTINGS UL/cUL listed Listed to U.S. and Canadian safety standards for wet locations.

COLOR TEMPERATURE:	4K
OPERATING TEMPERATURE:	-40°C + 40°C
CRI:	80+
LUMEN OUTPUT:	1200LM
WATTS:	18W
LED LIFE:	50,000 hours
WARRANTY:	5 years
VOLTAGE:	120V

APPLICATIONS

The high performance LED entry light features a sleek silhouette with long-lasting, energy-saving LED technology. It offers safety and security ideal for yards, lots, driveways, walkways, loading areas and other outdoor applications.

SPECIFICATION SHEETS

OS500LED

OUTDOOR SECURITY SOLUTIONS FOR RESIDENTIAL APPLICATION

DIMENSIONS

RATINGS

c UL us LISTED

WET LOCATIONS

ORDERING GUIDE

OS500 SERIES

Series	Finish
OS500LED-ELD	**DB** Dark Bronze

Notes: Configure product using **BOLD** options: Ex: **OS500LED-ELD-DB**