

OS1100LED

OUTDOOR SECURITY SOLUTIONS FOR COMMERCIAL APPLICATION



NAME:	
TYPE:	
DATE:	
NOTES:	

SPECIFICATIONS

LIGHT UNIT:	Rugged cast-aluminum, corrosion-resistant housing in dark bronze paint for lasting durability.
	LED lamp head is isolated from the driver. It is located in the rear housing, promoting a long service life.
	The lens is sealed to keep out moisture, dirt and bugs.
	Replaces an equivalent 150W Metal Halide luminaire.
	LEDs maintain 70% of light output at 100,000 hours of service life.
INSTALLATION:	Easily mounts to a recessed junction box or for a surface mounting, conduit entry ports are offered. - three(3) conveniently located 1/2" threaded conduit entry ports.
	The unit offers an easy-hold design for hands-free installation.
ELECTRICAL:	Energy efficient LED provides 2500 lumens, consumes 25W utilizing 120-277V driver.
	Rated for outdoor installations, -40°C minimum ambient.
	LISTINGS UL/cUL and DLC listed Listed to U.S. and Canadian safety standards

COLOR TEMPERATURE:	5k
OPERATING TEMPERATURE:	-40°C + 40°C
CRI:	80+
LUMEN OUTPUT:	2500LM
WATTS:	25W
LED LIFE:	100,000 hours
WARRANTY:	5 years
VOLTAGE:	120-277V
METAL HALIDE EQUIVALENT:	150W


APPLICATIONS

The high-performance LED Low Profile Wall pack offers security and general lighting for outdoor commercial applications. This energy saving illumination has an easy-hold design for hands-free installation and is ideal for building perimeters, loading docks, parking lots and other outdoor applications.

OS1100LED

OUTDOOR SECURITY SOLUTIONS FOR COMMERCIAL APPLICATION

DIMENSIONS



RATINGS



ORDERING GUIDE

OS1100 SERIES

Series	Finish
OS1100LED-SWP	DB Dark Bronze

Notes: Configure product using **BOLD** options: Ex: **OS1100LED-SWP-DB**